



Soft-Touch Texture Blocks

YARN SPECIFICATIONS

Description	Cut/Uncut Pile
Traffic	Residential/Light Commercial
Warranty	Lifetime
Fiber Type	100% ANSO BCF Nylon

FABRIC FINISHING

Dye Method	Continuous Dyed
Heat Set Treatment	2 Ply heat set
Soil Release Treatment	Carpet Guard®

FABRIC CONSTRUCTION

Finished Face Weight	25.0 oz./sq. yd.
Yarn Ply	2 ply
Stitches/Rows	11.0/inch
Gauge	1/8 ga.
Finished Pile Thickness	0.370 inches
Tufting Density	121.0/tufts/sq. inch
Primary Backing	Polypropylene
Secondary Backing	ClassicBac
Total Weight	60 oz./sq. yd.

PERFORMANCE SPECIFICATIONS

Density	2432 oz. / cu. yd
Traffic Performance	
Static Electricity	Static Resistance (AATCC-134)
Traffic	Recommended for residential & light commercial
Flammability	
Radiant Panel	ASTM-E648-08 (Class I)
NBS Smoke Chamber	ASTM-E662
Methanimine Tablet	Self extinguishing (DOC-FF-1-70)

1. Specifications subject to normal manufacturing tolerances and may be changed without prior notice.
2. Acceptance of orders subject to Carpets for Kids conditions of sale.
3. Serging excluded from 10-year wear warranty.